



SBU™

Solvent Based Urethane

Description

SBU™ is a clear 2 component solvent based urethane protective coating with strong abrasion and chemical resistance. It is suitable for outdoor weathering and is UV stable.

Available in 3 gal. /11.356L & 15 gal. /56.78L kits.

Recommended Uses

SBU™ solvent based urethane is used as a high performance protective coating over concrete, masonry, wood and metal surfaces indoors and outdoors.

Advantages

- Cost effective.
- UV resistant.
- Highly abrasion and chemical resistance.
- Non-yellowing
- VOC compliant.
- Available in clear and colored formulations. - See color chart for options.

Characteristics	Liquid
Color	Clear /Colored
VOC	-488g/l
Solid Content	53%
Ratio	2:1
Coverage	400 sqft per/gl
Cure schedule	
Application Temp	
Pot Life	2-5 hrs
Tack free	2-4 hrs
Recoat / Topcoat	4-8 hrs
Light Foot Traffic	14-24 hrs
Full cure	3-5 days
Mil Thickness	3-5 mils
Finish Characteristics	HighGloss >80 @60 degrees
Abrasion Res.	Calibrase wheel with 1000 gram total load and 500 cycles = 20.0 mg loss
Impact Res.	160 in. lb passed
Flexibility	No Cracks on 1/8" Mandrel
Adhesion	360 psi
Viscosity	Mixed 200-400cps

Disclaimer: The info herein is general to assist our customers in determining whether TruCrete Surfacing Systems® products are suitable for their specific applications. TruCrete Surfacing Systems® products are intended for sale to trained installers. We recommend that customers inspect and test our products before use to satisfy themselves as to the content and suitability for the applications they intend to use TruCrete Surfacing Systems® products for. Nothing herein shall constitute any warranty expressed or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

TruCrete Inc® All Rights Reserved
443-205-4547: info@trucrete: www.trucrete.com

Technical Data Sheet